

PRODUCT DATA

tensid[®] uk ltd

Limestone and Masonry Afterwash

Neutralising & brightening cleaner
for use with 766 Prewash

Description and use

Limestone and Masonry Afterwash, a mild organic acid cleaning compound, neutralises and brightens surfaces that have been prewashed with 766 Limestone and Masonry Prewash. When used properly, this two part cleaning system removes heavy carbon dirt and other atmospheric stains from porous limestone, concrete and most other porous masonry surfaces. 766 Limestone and Masonry Prewash and Limestone and Masonry Afterwash will not damage most masonry surfaces.

Advantages

- Does not contain hydrochloric or hydrofluoric acid
- Concentrated for economy
- Easy to apply with brush, roller or sprayer
- Following use of 766 Limestone and Masonry Prewash, test PROSOCO Light Duty Restoration Cleaner, Restoration Cleaner or Heavy Duty Restoration Cleaner to determine the most effective cleaning system.

Preparation

Protect surrounding surfaces and beware of wind drift. Cleaning effectiveness is reduced when surface and air temperatures fall below 10°C. Do not apply when temperatures are below -1°C. If freezing conditions exist prior to application, allow adequate time for masonry to thaw.

Equipment

Apply using a soft fibred masonry brush or low pressure compression sprayer. Rinse using a pressure washer.

Pretesting

Always test each type of surface and stain before overall application to ensure suitability, dilution rates and desired results. Apply test area according to the following application procedures. Allow area to dry thoroughly before inspection and approval.

TECHNICAL DATA

Appearance: Clear liquid

pH Value: 1.1

Boiling Point: N/A

Dilutions

Dilute one part fresh water to one part concentrated cleaner before application. Pour water into empty bucket, then carefully add Limestone Afterwash. Never pour water into the cleaner.

Recommended as follows. Always test.

Substrate	Type		m ² per litre
Architectural Concrete Block	Smooth	Yes	2 – 3
	Split Faced	Yes	
	Burnished	Yes	
	Ribbed	Yes	
Marble Travertine Limestone	Polished	No	N/A
	Unpolished	Yes	3 – 5
Granite	Polished	No	N/A
	Unpolished	Yes	4 – 6
Sandstone	Unpolished	Yes	3 – 4
Slate	Unpolished	Yes	3 – 5
Fired Clay	Brick	Yes	3 – 4
	Tile	Yes	
	Terracotta	Yes	
	Pavers	Yes	
Concrete	Block	Yes	3 - 4
	Brick	Yes	
	Tile	Yes	
	Precast	Yes	
	Panels	Yes	
	Pavers	Yes	
	Cast in place	Yes	

Application Instructions

It is necessary to apply 766 Limestone and Masonry Prewash and Limestone and Masonry Afterwash as a two part cleaning system to completely restore and neutralise masonry surfaces.

1. Immediately after rinsing 766 Limestone and Masonry Prewash from the masonry surface, apply the prepared Afterwash to the wet surface.
2. Allow the Afterwash to remain on the surface for 3 to 5 minutes.
3. Pressure rinse from the bottom of the treated area to the top. Make sure to cover each portion of the masonry surface with the concentrated stream of water. To avoid streaking, keep wall surfaces immediately below area being cleaned running wet and free of cleaner rundown and residues

Coverage Rates

Coverage rates will vary according to surface porosity, texture and severity of staining.

Safety Information

Causes burns. Wear suitable PPE - goggles, face shield, protective clothing and gloves to avoid splash to bare skin or eyes. Always refer to material safety data sheet before use.

Packing

15 litre plastic container.

Shelf Life

Limestone and Masonry Afterwash may be stored for up to 3 years in a tightly sealed, unopened container.

This Product Data is compiled to be of assistance but is without guarantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.

For more information and photos please visit:

www.tensid.com

Share your project photos and news on the Tensid UK social media professional community pages:



tensid[®] uk ltd

Limestone and Masonry Afterwash

REVISION: 01 July 2015, N^o.2