

PRODUCT DATA

tensid[®] uk ltd

Tavec 201

Effective, innovative, multi-layer paint stripper

Description and use

Tavec 201 is a biodegradable multiple layer paint stripper, formulated for removal of most paint types, urethanes and other coatings.

Advantages

- Can be used for most paint types
- Strips multiple layers of paint
- Non chemical paint waste
- Biodegradable

Recommended as follows. Always test.

Substrate	Type		m ² per litre
Marble Travertine Limestone	Polished	Yes	1 – 4
	Unpolished	Yes	1 – 3
Granite	Polished	Yes	1 – 4
	Unpolished	Yes	1 – 3
Sandstone	Unpolished	Yes	1 – 3
Slate	Unpolished	Yes	1 – 3
Fired Clay	Brick Tile Terracotta Pavers	Yes	1 – 3
Concrete		Yes	1 – 3
Wood		Yes	1 – 3
Glass		Yes	1 – 4

Preparation

Protect surrounding surfaces and beware of wind drift. Extended dwell times may be required at temperatures below 10°C. Application not recommended when temperatures are 5°C or below.

Equipment

Apply with a chemical resistant brush or airless spray equipment
Pressure - 2000 psi
Nozzle - 0.021 - 0.031
Spray tip - 65 - 80 degree

TECHNICAL DATA

Appearance: Greenish creamy paste

pH Value: 9 - 11

Boiling Point: N/A

Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

Application Instructions

1. Apply a uniform coating of Tavec 201 so the paint is no longer visible to a dry surface. The most effective method is by airless sprayer, however a brush can be used.
2. Allow the stripper to remain on the surface for 30 minutes – 24 hours. On multiple layers it may be necessary to remove the lifted layers and re-apply the product.
3. Do not allow the product to dry on the surface.
4. Pressure rinse with water. Hot water may improve the efficiency of stripping. Alternatively, remove dissolved paint with a spatula and rinse area thoroughly with clean water.
5. Re-application may be necessary, but ensure surface is dry prior to application of the stripper.
6. Do not allow product to come into contact with rubber or plastic.

Coverage Rates

Approximately 2 - 4 m² per litre. Coverage rates will vary according to the character of the surface.

Safety Information

Wear suitable PPE – Chemical resistant goggles and neoprene/rubber gloves to avoid splash to bare skin or eyes. Always refer to material safety data sheet before use.

Packing

5 litre plastic container

20 litre plastic container

Shelf Life

Tavec 201 may be stored for up to 1 year in a tightly sealed, unopened container, and in a frost free environment.

This Product Data is compiled to be of assistance but is without gurantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.

For more information and photos please visit:

www.tensid.com

Share your project photos and news on the Tensid UK social media professional community pages:



tensid[®] uk ltd

Tavec 201 Paint Stripper

REVISION: 01 July 2015, N^o.2