

PRODUCT DATA

tensid[®] uk ltd

Traffic Film Remover

General purpose, highly dilutable TFR

Description and use

TFR is a high active traffic film remover for use in or in combination with high pressure cleaners. It can be used on masonry surfaces but more specific products may be required, please see the Prosoco range of stone cleaners.

Equipment

Apply with brush or low compression sprayer or through a detergent feed on a pressure washer.

Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

Dilution

Highly dilutable but always test first in order to achieve the best results.

Application instructions

1. Apply from the bottom up
2. Agitate the surface with a brush
3. Allow to dwell for suitable period.
4. Rinse with high pressure washer.

If using a detergent feed on a pressure washer start with detergent feed set at 1% - 2%.

TECHNICAL DATA

Appearance: orange-brown liquid

pH Value: 12.5 - 14

Boiling Point: 100°C

Coverage Rates

Coverage rates will vary according to the character of the surface.

Packing

15 litre plastic container

Safety Information

Wear suitable PPE – goggles and gloves to avoid splash to bare skin or eyes.
Always refer to safety data sheet before use.

Shelf Life

TFR may be stored for up to 1 year in a tightly sealed, unopened container, and in a frost free environment.

This Product Data is compiled to be of assistance but is without gurantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.

For more information and photos please visit:

www.tensid.com

Share your project photos and news on the Tensid UK social media professional community pages:



tensid[®] uk ltd

Traffic Film Remover

REVISION: 01 July 2015, N^o.2