

## PRODUCT DATA

# tensid<sup>®</sup> uk ltd

## Cladex Prime

Primer for Cladex Restore

### Description and use

Cladex Prime is a surface Primer and sealer, part of the Cladex cladding restoration system. Cladex Prime is used for priming porous and weathered anodised aluminium prior to application of Cladex Restore.

### Advantages

- Soft water based solution
- Quick drying
- Economical

### Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

### Equipment

Use Cladex applicator. Alternatively a brush can be used for smaller areas.

### Application Conditions

Minimum air temperature 10°C  
Maximum relative humidity 90%  
Minimum surface temperature 10°C  
Maximum surface temperature 35°C

### Coverage Rates

With a typical 8 to 10 micron film thickness – 24 to 26m<sup>2</sup>

### TECHNICAL DATA

**Appearance:** Milky waterborne liquid

**pH Value:** 8.3

**Boiling Point:** N/A

### Application Instructions

1. Clean and degrease the surface with Cladex HD or Cladex LD, depending upon the degree and type of soiling.
2. Rinse with clean water and allow the surface to dry.
3. Shake the product prior to use. Apply a thin coat using cross link action i.e. top to bottom and right to left movements.  
Always use top to bottom as final action.
4. The product can be diluted up to a maximum of 10% with clean water

### Drying Times

Dust dry: 30 minutes  
Tack free: 30 minutes  
Touch dry: 30 minutes  
Over coatable: 1 hour

### Safety Information

Wear suitable PPE – goggles and gloves to avoid splash to bare skin or eyes. Always refer to material safety data sheet before use.

## Shelf Life

Cladex Prime may be stored for a minimum of 6 months in a tightly sealed, unopened container. Store in an ambient temperature not below 0°C

## Packing

1 x 10 litre plastic container  
or above 300C. Protect from frost.

*This Product Data is compiled to be of assistance but is without gurantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.*

For more information and photos please visit:

**[www.tensid.com](http://www.tensid.com)**

Share your project photos and news on the Tensid UK social media professional community pages:



**tensid<sup>®</sup> uk ltd**

REVISION: 01 July 2015, N<sup>o</sup>.2