

PRODUCT DATA

tensid[®] uk ltd

AGS Graffi Ghost Poultrice[®]

For deep seated and stubborn ghosting

Description and use

AGS Graffi Ghost Poultrice is a paste product ghosting remover. It works by oxidising away traces of pigments and by breaking down grease and oil residues in the substrate.

The poultrice is specially formulated for the removal of difficult ghosting and is suitable for most surfaces.

Advantages

- Fast acting and effective on most masonry surfaces
- Not effective if initial graffiti removal procedures have not been followed

Recommended as follows. Always test.

Substrate	Type		m ² per litre
Concrete		Yes	0.2 - 1
Marble Travertine Limestone	Polished*	Yes	0.2 - 1
	Unpolished	Yes	0.2 - 1
Granite	Polished*	Yes	0.2 - 1
	Unpolished	Yes	0.2 - 1
Sandstone	Unpolished	Yes	0.2 - 1
Slate	Unpolished	Yes	0.2 - 1
Fired Clay	Brick	Yes	0.2 - 1
	Tile	Yes	0.2 - 1
	Terracotta	Yes	0.2 - 1
	Pavers	Yes	0.2 - 1
Wood		No	

* Test first.

* This product has a bleaching effect on fabric and some other non masonry surfaces.

Preparation

Protect surrounding surfaces.

TECHNICAL DATA

Appearance: When mixed, yellow/brown paste

pH Value: 13 - 14

Boiling Point: N/A

Equipment

Apply with a brush or trowel.

Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

Application Instructions

1. Mix powder with liquid to make up a creamy consistency.
2. With a brush or trowel, apply the poultrice on affected areas.
3. Cover with black polythene and leave for up to 24 hours.
4. Remove poultrice with a plastic spatula or trowel.
5. Rinse off with hot water pressure washing.
6. On non polished masonry surfaces, use Graffi Ghost Rinse or PROSOCO Limestone Afterwash.
7. Repeat the process if ghosting remains.

Coverage Rates

Coverage rates will vary according to the character of the surface.

Packing

1 x 20 litre plastic container 1 x 4.5 kg powder

Safety Information

Wear suitable PPE – goggles and gloves to avoid splash to bare skin or eyes. Always refer to material safety data sheet before use.

Always rinse substrate clean of any other chemicals prior to application of Graffi Ghost Poulitice. Never mix liquid component with other substances.

Shelf Life

Graffi Ghost Poulitice may be stored for up to 1 year in a tightly sealed, unopened container.

This Product Data is compiled to be of assistance but is without guarantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.

For more information and photos please visit:

www.tensid.com

Share your project photos and news on the Tensid UK social media professional community pages:



tensid[®] uk ltd

AGS Graffi Ghost Poulitice

REVISION: 01 July 2015, N^o.2