

PRODUCT DATA

tensid[®] uk ltd

Tavec 100

Effective, innovative, multi-layer paint stripper

Description and use

Tavec 100 is a biodegradable multiple layer paint stripper, formulated for removal of most paint types, urethanes and other coatings.

Advantages

- Can be used for most paint types
- Strips multiple layers of paint
- Biodegradable

Recommended as follows. Always test.

Substrate	Type		m ² per litre
Marble Travertine Limestone	Polished	Yes	1 – 4
	Unpolished	Yes	1 – 3
Granite	Polished	Yes	1 – 4
	Unpolished	Yes	1 – 3
Sandstone	Unpolished	Yes	1 – 3
Slate	Unpolished	Yes	1 – 3
Fired Clay	Brick Tile Terracotta Pavers	Yes	1 – 3
Concrete		Yes	1 – 3
Wood		Yes	1 – 3
Glass		Yes	1 – 4

Preparation

Protect people and surrounding areas and beware of splashing and wind drift. Mask sensitive areas with tape and plastic sheeting.

Equipment

Apply with a chemical resistant brush

TECHNICAL DATA

Appearance: White paste

pH Value: 9.5 - 10.5

Boiling Point: N/A

Pretesting

Always test each type of surface to ensure suitability and desired results. Apply test area according to the following application procedures.

Application Instructions

1. Remove loose paint.
2. Apply a uniform coating of Tavec 100 so the paint is no longer visible to a dry surface. Work from the bottom to top.
3. Allow the stripper to remain on the surface for 30 minutes – 24 hours. On multiple layers it may be necessary to remove the lifted layers and re-apply the product.
4. Cover with thin polythene sheeting to improve efficiency. Especially for a long dwell time and multiple layers.
5. Do not allow the product to dry on the surface.
6. Pressure rinse with water. Hot and superheated water may improve the efficiency of stripping. Alternatively, remove dissolved paint with a spatula and rinse area thoroughly with clean water.
7. Re-application may be necessary, but ensure surface is dry, prior to application of the stripper.
8. Do not allow product to come into contact with rubber or plastic.

Coverage Rates

Approximately 2 - 4 m² per litre. Coverage rates will vary according to the character of the surface.

Safety Information

Wear suitable PPE – Chemical resistant goggles and neoprene/rubber gloves to avoid splash to bare skin or eyes. Always refer to material safety data sheet before use.

Packing

1 x 5 or 1 x 20 litre plastic container

Shelf Life

Tavec 100 may be stored for up to 1 year in a tightly sealed, unopened container, and in a frost free environment.

This Product Data is compiled to be of assistance but is without guarantee. Users are responsible for safe working practices. Always refer to Material Safety Data Sheets (MSDS) for full information before using this product.

For more information and photos please visit:

www.tensid.com

Share your project photos and news on the Tensid UK social media professional community pages:



tensid[®] uk ltd

Tavec 100 Paint Stripper

REVISION: 01 July 2015, N^o.2